

UK  
Europe  
USA  
Israel  
Australia  
Far East



**PALRAM Polycarb Ltd.**

Unit 2, Doncaster Carr Ind. Est. White Rose Way  
Doncaster DN4 5JH, England  
Tel ► (44) 1302 360 161, Fax ► (44) 1302 344 121  
E-mail ► polycarb@palram.com  
Web site ► <http://www.palram.com>

*Thermoplastic Sheets for Construction, Industry, Advertising and Agriculture*

**Zenit Spol S.R.O**

**31.07.2023**

**PALSUN UV/PALTUF TOLERANCES**

In response to the request for information regarding the tolerances of our Palsun/Paltuf products, please see below parameters taken from the CE standard 16240 which Palram Polycarb manufacture in accordance with.

Characteristic	Test method	Requirement
Sheet thickness	5.1.4	The nominal sheet thickness of the sheet shall be declared in millimetres. The sheet thickness at any point shall not vary by more than: – $\pm 5\%$ of the declared nominal sheet thickness for nominal sheet thickness greater or equal to 2 mm and up or equal to 5 mm. – $\pm 10\%$ of the declared nominal sheet thickness for nominal sheet thickness greater than 5 mm. For sheets with patterned surfaces, the sheet thickness is the overall thickness of the sheet.
Sheet length and width	5.1.6	The sheet length/width shall be within the interval from 0 % to +0,30 % of the declared sheet length/width.
Mass per unit area	5.1.5	The nominal mass per unit area of the sheet shall be declared in grams per square metre. The mass per unit area of a sheet shall be not less than 95 % of the declared nominal mass per unit area.

**Kind Regards**

**Sorrelle Reed**

UK  
Europe  
USA  
Israel  
Australia  
Far East



**PALRAM Polycarb Ltd.**

Unit 2, Doncaster Carr Ind. Est. White Rose Way  
Doncaster DN4 5JH, England  
Tel ► (44) 1302 360 161, Fax ► (44) 1302 344 121  
E-mail ► [polycarb@palram.com](mailto:polycarb@palram.com)  
Web site ► <http://www.palram.com>

*Thermoplastic Sheets for Construction, Industry, Advertising and Agriculture*

**Quality Assurance Manager – Palram Polycarb LTD.**