

Data Sheet - PALFOAM™ LW

Low Weight Flat Foamed PVC Sheet



Product Definition

Extra low weight flat foamed PVC sheet

Thickness Range

2 to 10mm

Colors

White

Width (standard sizes)

1220 mm

1560 mm

2030 mm

- Custom colors and sizes are available upon request, possibly subject to minimum order size.

Flammability

Standard	Classification
EN 13501	B, s2, d0

- All the above depends on thickness, for additional information please contact PALRAM.

Typical Physical Properties

Property	Standard	Conditions	Unit	Value	
Thickness				3mm	10mm
Physical					
Specific gravity	ASTM D-792		g/cm ³	0.47	0.47
Water absorption	ASTM D-570	24 hr @ 23°C	%	0.5	0.8
Mechanical – Machine direction					
Flexural modulus	ASTM D-790		MPa	1000	
Shore hardness	ASTM D-790			30	
Thermal					
Service temperature range			C°	-10 to 55	
Heat deflection temperature	ASTM D-648	Load: 1.82 MPa	C°	59-63	
VICAT softening temperature	ASTM D-1525	Load: 1 Kg	C°	74-78	
Coefficient of linear thermal expansion	ASTM D-696		10 ⁻⁵ /°C	6.7	
Thermal conductivity	ASTM C-177		W/mk	0.07	
Electrical					
Surface resistance	ASTM D-257		Ohm	5X10 ¹⁵	
Volume resistance	ASTM D-257		Ohm-cm	2.6X10 ¹⁵	